

SPIDER-NAS

HARDWARE SPECIFICATIONS (VERSION 1.0)



www.crystalinstruments.com

INTRODUCTION

The Spider-NAS (Network Attached Storage) is a dedicated storage device that works with front-end modules from Crystal Instruments, including the Spider-80X, Spider-81, and Spider-DAQ. Eight high-speed data buses interface directly with each Spider front-end module. An Ethernet port is used to configure and control the Spider-NAS.

A high-performance removable Serial ATA (SATA) 2.5-inch hard disk is used as storage media. When recorded, data will be written in NTFS file format. Data is extracted from the Spider-NAS using Crystal Instruments software to transfer data to the PC. Alternatively, the SATA hard disk can be physically removed and connected to extract data to the PC.

A second SATA hard-disk can be attached to Spider-NAS. This disk can serve the same purpose as the first disk. The user can plug-in his own 2.5-inch hard-drive for use.

When the Spider-NAS is shipped from the factory, a solid state hard-drive with a capacity of 250GB is installed internally. The solid state drive performs very well in the high shock and vibration environment.

Each dedicated data port can reach a theoretical speed of 480 Mbits/second. In practice, the system can store the data simultaneously for all dynamic measurement channels at 100 kHz sampling rate enabled.

A special error-checking algorithm developed by Crystal Instruments detects and avoids any errors that may occur in the data transfer and storage.

PRODUCT DATA

MECHANICAL PARAMETERS		
Ports	Data Ports	<ul style="list-style-type: none"> 8 ports 480 Mbits/second per port
	Ethernet	<ul style="list-style-type: none"> 1 port RJ45 Ethernet port that supports 10, 100, and 1000 Mbit/s line speed full or half duplex and autosensing
	SATA	<ul style="list-style-type: none"> 2 ports, one internal one external In default a 250GB SATA solid state hard-drive is installed internally SATA connectors that support data transfer speeds up to 3 Gbps
Storage Media		<ul style="list-style-type: none"> Two 2.5-inch SATA hard-drives
Power		<ul style="list-style-type: none"> 110 – 250 VAC Input, 15 VDC output, Max Amps 3 A, Lemo connector
Size (H x W x D)		<ul style="list-style-type: none"> 35 x 243 x 177 mm (1.38 x 9.57 x 6.97 inches)
System Weight		<ul style="list-style-type: none"> 1.30 kg
ENVIRONMENTAL RANGES		
Humidity		<ul style="list-style-type: none"> Operating humidity: 0% to 95% relative humidity, non-condensing
Temperature		<ul style="list-style-type: none"> Operating: 0 to 60°C (32 to 140°F) Non-operating: -10 to 70°C (14 to 158°F)
Shock		<ul style="list-style-type: none"> Operating: 20 g, 6 ms half-sine Non-operating: 33 g, 11 ms, Half sine
Vibration		<ul style="list-style-type: none"> Operating: 0.5 g sine, 0.4 grms random, 5 to 500 Hz Non-operating: 2.0 g sine, 1.1 grms random, 5 to 500 Hz
POWER CONSUMPTION		
System power consumption		<ul style="list-style-type: none"> Average: 10.5 Watts Peak: 17.8 Watts
Input voltage range		<ul style="list-style-type: none"> 10.8 – 18 VDC
SAFETY CERTIFICATIONS		
Complies with the following safety certifications:		<ul style="list-style-type: none"> Nemko EN60950:2000 TUV EN60950:2000 / IEC60950:1999 Low Voltage Directive (73/23/EEC) for CE Marking in European Union
DATA STORAGE FUNCTIONS		
General Functions		<ul style="list-style-type: none"> NTFS file system: Support single large data file (2 TB max) Data format: ASAM ODS data format Data point is in 32 bit single precision floating point Data file access: EDM, FTP, Removable disk Configuration Tool: EDM software from Crystal Instruments
Storage Speed		<ul style="list-style-type: none"> With 64 channels, each channel can reach 100 kHz sampling speed with 32 bits single precision floating point format. Aggregated speed is larger than 26 MB/second
Management		<ul style="list-style-type: none"> Wake-on LAN, Keyboard Power-on, Timer Power-on System power management, AC power failure recovery Watch Dog Timer

ANALOG
DIGITAL



GERÄTE UND SYSTEME FÜR
FORSCHUNG • ENTWICKLUNG • VERSUCH • SERVICE

ADM Messtechnik GmbH & Co. KG

Zum Wartturm 9 · 63571 Gelnhausen

Tel. (06051) 916557-1 · Fax 916557-9

sales@adm-messtechnik.de

**CRYSTAL INSTRUMENTS -
HEADQUARTERS**

2370 OWEN STREET

SANTA CLARA, CA 95054, USA

PHONE: +1-408-986-8880

FAX: +1-408-834-7818

EMAIL: SALES@GO-CI.COM

WWW.CRYSTALINSTRUMENTS.COM

© 2014 Crystal Instruments Corporation. All Rights Reserved. 01/2014

Crystal Instruments | 2370 Owen Street | Santa Clara, CA 95054 | support@go-ci.com | www.crystalinstruments.com

Notice: This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered or to be offered by Crystal Instruments. Crystal Instruments reserves the right to make changes to this document at any time, without notice, and assumes no responsibility for its use. This informational document describes features that may not be currently available. Contact a Crystal Instruments sales representative for information on features and product availability.